

beko® 



CEMENT	PLASTIC	WOOD	BRICK
METAL	MDF / CHIP	PORCELAIN	STONE

- ✓ **BONDS LARGE VARIETY OF MATERIALS**
- ✓ **SINGLE-COMPONENT**
- ✓ **NO PRIMER REQUIRED**
- ✓ **FROST-PROOF**
- ✓ **USABLE WITH NATURAL STONE**
- ✓ **FULLY CURES IN JUST 7 TO 10 MINUTES**
- ✓ **HOLDS 130KGS PER SQ CM**
- ✓ **OPENED CARTRIDGE LASTS UP TO 18 MONTHS**
- ✓ **INDOOR AND OUTDOOR APPLICATION**

**THE
ORIGINAL**



Scan to watch a video on Allcon10

Available in -
150ml [260 100 150EN]
310ml [260 100 310EN]

THE *ALLCON 10*® CONSTRUCTION ADHESIVE

AVAILABLE IN STORE OR ONLINE



HOW TO APPLY :

STEP 1



CLEAN SURFACE

STEP 2



**DAMPEN OR SPRAY SURFACE
[IF REQUIRED]**

STEP 3



GLUE & CLAMP

Technical data

Basis	Moisture-curing polyurethane
Processable	from +5° C to max. +40° C
Temperature	resistant from -40° C to max. +80° C (short term: +120° C)
Skin formation time	approx. 3 minutes under standard conditions (+23° C / 50% relative air humidity)
Curing	approx. 3 mm Allcon 10 per 24 hours; approx. 70% surface bonding after 7 to 10 minutes; 100% cured after 30 to 45 minutes
Gap bridging	approx. 1,0 cm
Colour	beige
Smell	low odour
Density	approx. 1,4 g/cm³
Viscosity	pasty
Tested	test report in accordance with DIN EN 204 D4 (waterproof gluing), according to WATT 91 (+80° C)
Storage life	opened cartridge can be used for up to 10 months, unopened cartridge lasts for up to 1 ½ years
Storage	dry, at room temperature