

**WALTHER
STRONG®**



**IF YOU'RE A PROFESSIONAL
YOU'RE USING WALTHER STRONG**


beko® 




- ✓ UV & aging resistant
- ✓ 80% instant grab strength
- ✓ Weather-proof & water-proof
- ✓ Doesn't shrink or crack
- ✓ Indoor & outdoor use
- ✓ Works in wet or dry conditions
- ✓ Conforms to food prep standards
- ✓ Controlled resistance to fungal & bacteria
- ✓ Excellent resistance to chemicals




WHITE



TRANSPARENT



GREY



BEIGE



BLACK

ULTIMATE WATERPROOF & FLEXIBLE ADHESIVE
MS-FLEX SEALANT & ADHESIVE® 300ML

AVAILABLE IN STORE OR ONLINE



HOW TO APPLY MS-FLEX SEALANT & ADHESIVE® :

STEP 1



Ensure surface is free
from debris and dust

STEP 2



Apply in dots or
waves on one side

STEP 3



Press surfaces
together firmly



Wood



Metal



Plastic



Glass



Aluminium



Polystyrene



Rigid PVC



Ceramic



Concrete



Stone

Technical data

	coloured	transparent
Basis	MS-Polymer	MS-Polymer
Processable	from +5° C to max. +40° C	from +5° C to max. +45° C
Temperature	resistant from -40° C up to +90° C	resistant from -60° C up to +80° C
Skin formation time	approx. 10 to 15 min. under standard conditions	approx. 8 to 20 min. under standard conditions
Curing	approx. 2 mm/24 hours depending on the temperature	approx. 1 to 2 mm/24 hours depending on the temperature
Density	approx. 1,5 g/cm ³	approx. 1,0 to 1,05 g/cm ³
Shore A hardness	approx. 60	approx. 45 +/- 5
Flexibility	+/- 15%	approx. 20%
Elongation at break	approx. 200%	approx. 250%
Tensile strength	approx. 2,8 N/mm ²	approx. 0,85 N/mm ²
Storage life	unopened 12 months, apply quickly after opening	
Storage	keep in a cool, dry place at +5° C to +30° C, protect from frost and heat	