

Product Description:

Walther Strong 50MM Masking Tape is a general-purpose masking tape for holding, bundling, sealing, general paint masking and a vast number of other jobs where a pressure sensitive tape is needed.

Product Features:

- Tape has been tested and found to meet the requirements of ASTM D 6123 / D 6123M-97. 3M does not test each lot for compliance to this specification.
- Rubber adhesive for instant adhesion that sticks easily and helps reduce labour.
- Good holding power to help resist lifting or curling.
- Crepe paper backing that is conformable to maintain integrity when formed around a corner.
- Easy tear and sliver resistant
- Good paint hold-out that resists bleed-through.
- Controlled unwind.
- Tape may become very difficult to remove if subjected to prolonged outdoor exposure.

Technical Information Note:

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties -

Total Tape Thickness - 0.13 mm 5.2 ml ASTM D3652

Adhesive Type - Rubber

Typical Performance Characteristics:

- 180° Peel Adhesion
- 3.1 N/cm
- 28 oz/in
- ASTM D3330
- 12 in/min (300 mm/min)

Tensile Strength –

- 40.3 N/cm
- 23 lb/in
- ASTM D3759

Elongation at Break –

- 8 %
- ASTM D3759

Short Term Temperature Resistance –

93 °C/200 °F

Available Sizes:

25MMx50M, 38MMx50M, 50MMx50M

Storage and Shelf Life:

- Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.
- To obtain best performance, use within 18 months from date of manufacture.

